



Revision Number: 001.1

Issue date: 05/04/2023

1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Product identifier used on the label: FP Kenra Platinum Silkening Mist 80% VOC

Recommended use of the chemical and restrictions on use: Hairspray, Aerosol

Name, address and telephone number of the chemical manufacturer:

Henkel Corporation
One Henkel Way
Rocky Hill CT 06067

CHEMTREC: 1-800-424-9300 (24 hours daily)
Internet: www.henkel-northamerica.com

Emergency telephone number: Medical Emergencies:1-800-258-3425

2. HAZARDS IDENTIFICATION

The hazards described in this Globally Harmonized System Safety Data Sheet (SDS) are not intended for consumers, and does not address consumer use of the product. For information regarding consumer applications of this product, refer to the product label.

Classification of the substance or mixture in accordance with paragraph (d) of §1910.1200

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL	2
GASES UNDER PRESSURE	Liquef. Gas
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

Signal word, hazard statement(s), symbol(s) and precautionary statement(s) in accordance with paragraph (f) of §1910.1200

Signal word: WARNING

Hazard Statement(s):

Flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Symbol(s):



Precautionary Statements:

Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash affected area thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves, eye protection, and face protection.

Response:

IF ON SKIN: Wash with plenty of water.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin irritation occurs: Get medical attention.

If eye irritation persists: Get medical attention.
Take off contaminated clothing.
Storage: Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Disposal: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Hazards not otherwise classified: Not available.

Percentage of ingredient(s) with unknown toxicity:
21 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

The following chemicals are classified as health hazards in accordance with paragraph (d) of § 1910.1200.

Chemical Name*	CAS Number (Unique Identifier)	Concentration
Isobutane	75-28-5	>= 30 - < 50 %
Ethanol denatured	64-17-5	>= 20 - < 30 %
2,2,4,6,6-Pentamethylheptane	13475-82-6	>= 5 - < 10 %
propane	74-98-6	>= 5 - < 10 %

*The specific chemical identity and/or exact percentage (concentration) of composition has been withheld because a trade secret is claimed in accordance with paragraph (i) of §1910.1200.

Actual concentration or concentration range is withheld as a trade secret

4. FIRST AID MEASURES

Description of necessary measures

Inhalation: If inhaled, immediately remove the affected person to fresh air.
Skin contact: First aid measures not required. Cosmetic product and therefore not necessary.
Eye contact: Rinse eyes immediately with plenty of water, occasionally lifting upper and lower lids, until no evidence of product remains. Get medical attention if pain or irritation develops.
Ingestion: Dilution by rinsing the mouth and giving water or milk to drink is generally recommended. Contact physician or local poison control center.

Most important symptoms and effects, both acute and delayed

After eye contact: May cause moderate to severe irritation. After skin contact: Repeated or prolonged excessive exposure may cause irritation or dermatitis. After inhalation: Breathing high vapor concentrations may produce anesthetic effects, nausea, dizziness, headache. After ingestion: Ingestion may cause irritation of mouth, throat, digestive tract, diarrhea and vomiting.

Indication of any immediate medical attention and special treatment needed

After eye contact: Rinse eyes with plenty of water until no evidence of product remains. After skin contact: Rinse affected area with large amounts of mild soap and water until no evidence of product remains. After inhalation: Remove from exposure area to fresh air. After ingestion: Administer immediately plenty of water. With ingestion of larger quantities (in adults one tablespoon) or in the case of discomfort or pain seek immediate medical attention.

5. FIRE FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Dry chemical, carbon dioxide, water spray or regular foam.
Unsuitable extinguishing media: None known

Specific hazards arising from the chemical

carbon oxides. nitrogen oxides

Special protective equipment and precautions for fire-fighters

In case of fire, wear a full-face positive-pressure self-contained breathing apparatus and protective suit. Shut off all ignition sources. Apply cooling water to sides of containers that are exposed to flames until well after fire is out. Isolate area. Keep unnecessary personnel away. Avoid breathing vapors, keep upwind.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear skin, eye and respiratory protection as recommended in Section 8. Stop leak if you can do it without risk. No smoking, flames or flares in hazard area! Spills present a slipping hazard. Keep unnecessary personnel away. Ventilate spill area if possible. Make sure area is slip-free before re-opening to traffic.

Environmental precautions

Small or household quantities may be disposed in regular domestic trash. For larger quantities check with your local disposal authorities.

Methods and materials for containment and cleaning up

SMALL SPILLS: Contain and absorb with sand or other non-combustible absorbent material and place into containers for later disposal. Wash site of spillage thoroughly with water. LARGE SPILLS: Shut off ignition sources. Stop leak if you can do it without risk. Use water spray to reduce vapors. Isolate area until vapors have dispersed. No smoking, flames or flares in hazard area! Keep unnecessary people away; isolate hazard area and deny entry. Ventilate closed spaces before entering.

7. HANDLING AND STORAGE

Precautions for safe handling

Do not take internally. Use with adequate ventilation. Keep the containers closed when not in use. Have emergency equipment (for fires, spills, leaks, etc.) readily available.

Conditions for safe storage, including any incompatibilities

Store in original containers in a cool dry area. Store away from excessive heat and incompatible substances. Storage areas for large quantities (warehouse) should be well ventilated. Keep the containers tightly closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Isobutane	1,000 ppm STEL	None	None	None
Ethanol denatured	1,000 ppm STEL	1,000 ppm (1,900 mg/m3) PEL	None	None
2,2,4,6,6-Pentamethylheptane	None	None	None	None
propane	D: Simple asphyxiant, EX: Explosion hazard (Simple asphyxiant.)	1,000 ppm (1,800 mg/m3) PEL	None	None

Appropriate engineering controls

Provide local exhaust or general dilution ventilation to keep exposure to airborne contaminants below the permissible exposure limits where mists or vapors may be generated.

Individual protection measures

- Respiratory:** Air contamination monitoring should be carried out where mists or vapors are likely to be generated, to assure that the employees are not exposed to airborne contaminants above the permissible exposure limits.
- Eye:** Splash-proof safety glasses are required to prevent eye contact where splashing of product may occur.

Hand/Body: Protective gloves are required where repeated or prolonged skin contact may occur.
Protective clothing is required where repeated or prolonged skin contact may occur.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	aerosolLiquefied gas
Odor:	colourlesscolourless
Odor threshold:	characteristiccharacteristic
pH:	Not available.
Melting point/ range:	Not available.
Boiling point/range:	Not available.
Flash point:	10 °C (50°F) ASTM D56: Flash point in closed cup
Evaporation rate:	Not available.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Vapor pressure:	Not available.
Vapor density:	Not available.
Solubility in water:	Partially soluble
Partition coefficient (n-octanol/water):	Not available.
Autoignition temperature:	Not available.
Decomposition temperature:	Not available.
Viscosity:	Not available.
VOC content:	74 %

10. STABILITY AND REACTIVITY

Reactivity:	This product may react with strong acids, bases and oxidizing agents.
Chemical stability:	Stable under normal ambient temperature (70°F, 21°C) and pressure (1 atm).
Possibility of hazardous reactions:	Hazardous polymerization has not been reported to occur under normal temperatures and pressures.
Conditions to avoid:	Avoid contact with incompatible substances, excessive heat, flames or other ignition sources. Exposure to sunlight or heat may cause bursting. Do not place aerosol cans in trash compactor. Contents are under pressure; containers may violently rupture and travel a considerable distance. Do not permit physical damage or overheating of containers.
Incompatible materials:	Strong oxidizers and alkalies, chlorine, hypochlorites.
Hazardous decomposition products:	Thermal decomposition may produce irritating or poisonous gases.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure including symptoms related to characteristics

Inhalation:	Breathing high vapor concentrations may produce anesthetic effects, nausea, dizziness, headache, weakness, peripheral drowsiness.
Skin contact:	No adverse effects anticipated from normal use.
Eye contact:	May cause moderate to severe irritation.
Ingestion:	May cause mild gastrointestinal irritation with nausea, vomiting, diarrhea and abdominal pain.
Physical/Chemical:	The product is flammable.
Other relevant toxicity information:	This product is a personal care or cosmetic product. The use of this product by consumers is safe under normal and reasonable foreseen use.

Numerical measures of toxicity, including delayed and immediate effect

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Isobutane	Inhalation LC50 (RAT, 10 min) = > 800000 ppm Inhalation LC50 (RAT, 10 min) = 1,443 mg/l Inhalation LC50 (RAT, 10 min) = 1,442,738 mg/m3	Cardiac, Central nervous system, Lung
Ethanol denatured	Oral LD50 (RAT) = 9.9 g/kg Oral LD50 (RAT) = 6.2 g/kg Oral LD50 (RAT) = 17.8 g/kg Oral LD50 (RAT) = 11.5 g/kg Oral LD50 (RAT) = 10.6 g/kg Oral LD50 (RAT) = 7,060 mg/kg Inhalation LC50 (RAT, 6 h) = 92.6 mg/l Inhalation LC50 (RAT, 6 h) = 51.3 mg/l Inhalation LC50 (RAT, 4 h) = 133.8 mg/l Inhalation LC50 (RAT, 6 h) = 82.1 mg/l Inhalation LC50 (RAT, 4 h) = 124.7 mg/l Inhalation LC50 (RAT, 6 h) = 52.9 mg/l Inhalation LC50 (RAT, 6 h) = 54.8 mg/l Inhalation LC50 (RAT, 4 h) = > 115.9 mg/l Inhalation LC50 (RAT, 6 h) = 87.5 mg/l Inhalation LC50 (RAT, 4 h) = 130.7 mg/l Inhalation LC50 (RAT, 4 h) = 128.2 mg/l Inhalation LC50 (RAT, 4 h) = 116.9 mg/l	Central nervous system, Irritant
2,2,4,6,6-Pentamethylheptane	None	No Data
propane	Inhalation LC50 (RAT, 10 min) = 1,354,944 mg/m3 Inhalation LC50 (RAT, 4 h) = > 13023 ppm Inhalation LC50 (RAT, 10 min) = 1,355 mg/l Inhalation LC50 (RAT, 10 min) = 1,443 mg/l Inhalation LC50 (RAT, 10 min) = 570000 ppm Inhalation LC50 (RAT, 10 min) = 1,442,738 mg/m3 Inhalation LC50 (RAT, 10 min) = > 800000 ppm Inhalation LC50 (RAT, 4 h) = > 13023 ppm	Cardiac, Central nervous system, Irritant

Carcinogenicity information

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Isobutane	No	No	No
Ethanol denatured	No	No	No
2,2,4,6,6-Pentamethylheptane	No	No	No
propane	No	No	No

Carcinogenicity

None of the ingredients in this product are listed as carcinogens by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA).

Mutagenicity

None of the ingredients in this product are known to cause mutagenicity.

Toxicity for reproduction

None of the ingredients in this product are known as reproductive, fetal, or developmental hazards.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity:

This product is anticipated to be safe for the environment at concentrations predicted in household settings under normal use conditions. The following toxicity information is available for the hazardous ingredient(s) when used as technical grade and is provided as reference for the occupational settings.

Toxicity to fish:

The aquatic toxicity profile of this product has not been determined.

Chronic toxicity to aquatic invertebrates

The aquatic toxicity profile of this product has not been determined.

Toxicity to algae:

The aquatic toxicity profile of this product has not been determined.

Persistence and degradability

Hazardous substances CAS-No.	Result value	Route of application	Species	Method
Isobutane 75-28-5	readily biodegradable	aerobic	71.43 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
2,2,4,6,6- Pentamethylheptane 13475-82-6	not readily biodegradable.	aerobic	31.5 %	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Propane 74-98-6	readily biodegradable	aerobic	> 60 %	OECD 301 A - F

Bioaccumulative potential

The bioaccumulation potential of this product has not been determined.

Mobility in soil

The mobility of this product (in soil and water) has not been determined.

13. DISPOSAL CONSIDERATIONS

Description of waste residues:

Hazardous waste number: D001 (Ignitability)

Safe handling and disposal methods:

Recommended method of disposal: This product is a RCRA characteristic (ignitable) hazardous waste and must be disposed of in a RCRA Subtitle C landfill.

Disposal of uncleaned packages: Place in trash.

14. TRANSPORT INFORMATION

The information in this section is for reference only and should not take the place of a shipping paper (bill of lading) specific to an order. Please note that the proper shipping classification may vary by packaging, properties, and mode of transportation.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

15. REGULATORY INFORMATION

Occupational safety and health act: Hazard Communication Standard, 29 CFR 1910.1200(g) Appendix D: The Occupational Safety and Health Administration (OSHA) require that the Safety Data Sheets (SDSs) are readily accessible to employees for all hazardous chemicals in the workplace. Since the use pattern and exposure in the workplace are generally not consistent with those experienced by consumers, this SDS may contain health hazard information not relevant to consumer use.

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Not available.
CERCLA/SARA Section 313:	None above reporting de minimis.
California Proposition 65:	This product does not contain any Proposition 65 chemicals at levels requiring a warning in the State of California.

Canada Regulatory Information

CEPA DSL/NDSL Status:	One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.
------------------------------	---

16. OTHER INFORMATION

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: R&D Support Services

Issue date: 05/04/2023